



Part Number: 9923

Hook- Up/ Lead Wire UL AWM Style 1007 & 1569, (1) 24 AWG (7x32) TC, PVC, 300V 80°C, 300V 105°C

Request Sample
 Requ

Product Description

One 24 AWG stranded (7x32) tinned copper conductor, PVC insulation.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Mater	ial	No. of Conductors
24	7x32	TC - Tinned	Copper	1
Condu	uctor Count:		1	
Condu	uctor Size:		24 AWG	3

Insulation

Material	Nominal Diameter	Nominal Wall Thickness	Min. Average Wall Thickness
PVC - Polyvinyl Chloride	0.056 in	0.016 in	0.015 in

Outer Jacket Material

Material No Jacket

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
23.25 Ohm/1000ft
Shielding: Unshielded

-----g-

High Frequency (Nominal/Typical) Nom. Insertion Loss

6.3 dB/100m 6.3 dB/100m

Current

Element	Max. Recommended Current [A]
Single conductor in free air @ 30C ambient	7.0 A

Voltage

Non-UL Voltage Rating	UL Voltage Rating
300 V	300 V

Temperature Range

Non-UL Temp Rating:	105°C
UL Temp Rating:	105°C
Operating Temp Range:	-20°C To +105°C

Mechanical Characteristics

Bulk Cable Weight:	2.6 lbs/1000ft

Standards

UL Rating:	300V RMS, 80°C and 300V, 105°C
UL AWM Style:	UL Style 1007 (300 V 80°C), UL Style 1569 (300 V 105°C)
CSA Rating:	300V RMS, 105°C
CSA AWM Specification:	TRSR-64
CSA Type:	TRSR-64
Military Specification:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (EU.V): Yes EU Directive 2011/65/EU (ROHS II): Yes EU Directive 2011/65/EU (ROHS II): Yes EU Directive 2012/19/EU (WEEE): Yes EU Directive 2015/863/EU: Yes EU Directive 2015/863/EU: Yes EU Directive 2015/863/EU: Yes EU Directive 2015/863/EU: Yes EU CE Mark: Yes EU ROHS Compliance Date (Myy-mm-dd): Yes EU ROHS Compliance Date (Myy-mm-dd): Yes Ca Prop 65 (CJ for Wire & 2014): Yes HI Order #39 (China ROHS): Yes		
(BFR):resEU Directive 2011/65/EU (ROHS II):YesEU Directive 2012/19/EU (WEEE):YesEU Directive 2015/863/EU:YesEU Directive Compliance:EU Directive 2003/11/EC (BFR)EU CE Mark:YesEU ROHS Compliance Date (Vyyy-mm-dd):2005-10-01CA Prop 65 (CJ for Wire & Cable):Yes		Yes
(ROHS II): Tes EU Directive 2012/19/EU (WEEE): Yes EU Directive 2015/863/EU: Yes EU Directive Compliance: EU Directive 2003/11/EC (BFR) EU CE Mark: Yes EU ROHS Compliance Date (Vyyy-mm-dd): 2005-10-01 CA Prop 65 (CJ for Wire & Cable): Yes		Yes
(WEEE): Tes EU Directive 2015/863/EU: Yes EU Directive Compliance: EU Directive 2003/11/EC (BFR) EU CE Mark: Yes EU ROHS Compliance Date (yyy-mm-dd): 2005-10-01 CA Prop 65 (CJ for Wire & Cable): Yes		Yes
EU Directive Compliance: EU Directive 2003/11/EC (BFR) EU CE Mark: Yes EU RoHS Compliance Date (yyyy-mm-dd): 2005-10-01 CA Prop 65 (CJ for Wire & Cable): Yes		Yes
EU CE Mark: Yes EU ROHS Compliance Date (yyyy-mm-dd): Yes CA Prop 65 (CJ for Wire & Cable): Yes	EU Directive 2015/863/EU:	Yes
EU RoHS Compliance Date (yyyy-mm-dd): 2005-10-01 CA Prop 65 (CJ for Wire & Cable): Yes	EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
(yyyy-mm-dd): 2003-10-01 CA Prop 65 (CJ for Wire & Cable): Yes	EU CE Mark:	Yes
Cable):		2005-10-01
MII Order #39 (China RoHS): Yes		Yes
	MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
CSA Flammability:	FT1
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

|--|

Part Number

Variants

Item #	Color	Footnote
9923 010100	Black	
9923 0101000	Black	Р
9923 0105000	Black	С
9923 0131000	Blue, Dark	Р
9923 0011000	Brown	Р
9923 0081000	Gray	Р
9923 0051000	Green, Dark	Р
9923 0031000	Orange	Р
9923 002100	Red	
9923 0021000	Red	Р
9923 0025000	Red	Р
9923 0071000	Violet	Р
9923 009100	White	
9923 0091000	White	Р
9923 0041000	Yellow	Р

Footnote:	P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.	
Footnote:	C - CRATE REEL PUT-UP.	

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.